



This safety data sheet complies with the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Date 30-Jul-2019

Version 5

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code(s) 152PGF
Product name WHITE PEACH TYPE, NATURAL FLAVOR BLEND

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Ingredient for further processing

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufacturer Apex Flavors, Inc.
1371 Brass Mill Rd.
Suite A
Belcamp, MD 21017
(410) 565-6600

For further information, please contact:

E-mail Address cpisano@apexflavors.com

1.4. Emergency telephone number

Emergency telephone Chemtrec: 1-800-424-9300 for US/ 703-527-3887 outside US

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Serious eye damage/eye irritation	Category 2 - (H319)
Carcinogenicity	Category 1A - (H350)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Product identifier
Contains BENZYL ALCOHOL, ETHYL ALCOHOL



Signal Word

Danger

Hazard Statements

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H350 - May cause cancer

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P370 + P378 - In case of fire: Use .? to extinguish

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

2.3. Other information

No information available

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Chemical Name	EC-No	CAS-No	Weight %	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
ETHYL ALCOHOL	200-578-6	64-17-5	50-90%	Flam. Liq. 2 (H225) Eye Irrit. 1 (H319)	No data available
ETHYL ACETATE	Present	141-78-6	5-10%	Eye Irrit. 1 (H319) (EFFA) Flam. Liq. 2 (H225) (EFFA) Eye Irrit. 1 (H319) (EUH066) Flam. Liq. 2 (H225) STOT SE 3 (H336) Eye Irrit. 2 (H319)	No data available
BENZYL ALCOHOL	202-859-9	100-51-6	1-5%	Acute Tox. 5 (H333) Acute Tox. 4 (H302)	No data available
ISOAMYL ACETATE	Present	123-92-2	<1%	Aquatic Acute 3 (H402) (EFFA) (EUH066) Flam. Liq. 3 (H226)	No data available
ACETIC ACID	200-580-7	64-19-7	<1%	Skin Corr. 1A (314) Eye Dam. 1 (H318) Flam. Liq. 3 (H226)	No data available
HEXYL ALCOHOL	Present	111-27-3	<1%	Aquatic Acute 3 (H402) (EFFA) Eye Irrit. 1 (H319) (EFFA) Skin Irrit. 3 (316) (EFFA) Acute Tox. 4 (H302) (EFFA) Acute Tox. 4 (H312)(EFFA) Flam. Liq. 3 (H226)(EFFA) Acute Tox. 4 (H302)	No data available
BENZALDEHYDE	Present	100-52-7	<1%	Acute Tox. 4 (H302) Aquatic Acute 2 (H401) (EFFA) Eye Irrit. 1 (H319) (EFFA) Skin Irrit. 3 (316) (EFFA) Acute Tox. 4 (H302) (EFFA) Flam. Liq. 4 (H227)(EFFA) Acute Tox. 4 (H332)(EFFA) Aquatic Acute 2 (H401) Eye Irrit. 1 (H319) Skin Irrit. 3 (H316) Acute Tox. 4 (H302) Acute Tox. 4 (H332)	No data available
LIMONENE	227-813-5	5989-27-5	<1%	Aquatic Acute 1 (H400) Skin Sens. 1 (H317) Skin Irrit. 1 (H315) Asp. Tox. 1 (H304) Aquatic Chronic 1 (H410)	No data available

PINENES	201-291-9	80-56-8	<1%	Flam. Liq. 3 (H226) Aquatic Acute 1 (H400) Skin Sens. 1 (H317) Skin Irrit. 1 (H315) Asp. Tox. 1 (H304) Aquatic Chronic 1 (H410) Acute Tox. 5 (H303) Flam. Liq. 3 (H226)	No data available
---------	-----------	---------	-----	--	-------------------

For the full text of the R-phrases mentioned in this Section, see Section 16

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this material safety data sheet to the doctor in attendance.
Inhalation	Move to fresh air.
Skin contact	Wash off immediately with plenty of water.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Self-protection of the first aider	Remove all sources of ignition.

4.2. Most important symptoms and effects, both acute and delayed

Main Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures**Personal precautions**

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

6.3. Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE**7.1. Precautions for safe handling****Advice on safe handling**

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

General Hygiene Considerations

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

7.2. Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep tightly closed in a dry and cool place. Keep in properly labeled containers.

Incompatible products

None known based on information supplied.

7.3 Specific end use(s)**Risk Management Methods (RMM)**

The information required is contained in this Material Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Chemical Name	European Union	The United Kingdom	France	Spain	Germany
ETHYL ALCOHOL 64-17-5	-	STEL: 3000 ppm STEL: 5760 mg/m ³ TWA: 1000 ppm TWA: 1920 mg/m ³	VME: 1000 ppm VME: 1900 mg/m ³ VLCT: 5000 ppm VLCT: 9500 mg/m ³	VLA-ED: 1000 ppm VLA-ED: 1910 mg/m ³	-
ETHYL ACETATE 141-78-6	-	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 1400 mg/m ³	TWA: 400 ppm TWA: 1460 mg/m ³	-
ISOAMYL ACETATE 123-92-2	TWA 50 ppm TWA 270 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³	STEL: 100 ppm STEL: 540 mg/m ³	-

	STEL 100 ppm STEL 540 mg/m ³		STEL: 100 ppm STEL: 540 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³	
ACETIC ACID 64-19-7	TWA 10 ppm TWA 25 mg/m ³	-	VLCT: 10 ppm VLCT: 25 mg/m ³	VLA-EC: 15 ppm VLA-EC: 37 mg/m ³ VLA-ED: 10 ppm VLA-ED: 25 mg/m ³	-
PINENES 80-56-8	-	-	-	VLA-ED: 20 ppm VLA-ED: 113 mg/m ³	-
Chemical Name	Italy	Portugal	The Netherlands	Finland	Denmark
ETHYL ALCOHOL 64-17-5	-	TWA: 1000 ppm	Skin STEL: 1900 mg/m ³ TWA: 260 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³ STEL: 1300 ppm STEL: 2500 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³
ETHYL ACETATE 141-78-6	-	TWA: 400 ppm	-	TWA: 300 ppm TWA: 1100 mg/m ³ STEL: 500 ppm STEL: 1800 mg/m ³	TWA: 150 ppm TWA: 540 mg/m ³
BENZYL ALCOHOL 100-51-6	-	-	-	TWA: 10 ppm TWA: 45 mg/m ³	-
ISOAMYL ACETATE 123-92-2	TWA: 50 ppm TWA: 270 mg/m ³ STEL: 100 ppm STEL: 540 mg/m ³	STEL: 100 ppm STEL: 540 mg/m ³ TWA: 50 ppm	STEL: 530 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³ STEL: 100 ppm STEL: 540 mg/m ³	TWA: 50 ppm TWA: 271 mg/m ³
ACETIC ACID 64-19-7	-	STEL: 15 ppm TWA: 10 ppm	-	TWA: 5 ppm TWA: 13 mg/m ³ STEL: 10 ppm STEL: 25 mg/m ³	TWA: 10 ppm TWA: 25 mg/m ³
BENZALDEHYDE 100-52-7	-	-	-	TWA: 1 ppm TWA: 4.4 mg/m ³ STEL: 4 ppm STEL: 17.4 mg/m ³ Ceiling: 4 ppm Ceiling: 17.4 mg/m ³	-
LIMONENE 5989-27-5	-	-	-	TWA: 25 ppm TWA: 140 mg/m ³ STEL: 50 ppm STEL: 280 mg/m ³	-
PINENES 80-56-8	-	TWA: 20 ppm	-	-	-
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
ETHYL ALCOHOL 64-17-5	STEL 2000 ppm STEL 3800 mg/m ³ MAK: 1000 ppm MAK: 1900 mg/m ³	STEL: 1000 ppm STEL: 1920 mg/m ³ MAK: 500 ppm MAK: 960 mg/m ³	NDS: 1900 mg/m ³	TWA: 500 ppm TWA: 950 mg/m ³ STEL: 625 ppm STEL: 1187.5 mg/m ³	TWA: 1000 ppm TWA: 1900 mg/m ³
ETHYL ACETATE 141-78-6	STEL 600 ppm STEL 2100 mg/m ³ TWA: 300 ppm TWA: 1050 mg/m ³	STEL: 800 ppm STEL: 2800 mg/m ³ TWA: 400 ppm TWA: 1400 mg/m ³	STEL: 600 mg/m ³ TWA: 200 mg/m ³	TWA: 150 ppm TWA: 550 mg/m ³ STEL: 187.5 ppm STEL: 687.5 mg/m ³	TWA: 200 ppm STEL: 400 ppm
BENZYL ALCOHOL 100-51-6	-	-	NDS: 240 mg/m ³	-	-
ISOAMYL ACETATE 123-92-2	STEL 100 ppm STEL 540 mg/m ³ TWA: 50 ppm TWA: 270 mg/m ³	TWA: 50 ppm TWA: 260 mg/m ³	STEL: 500 mg/m ³ TWA: 250 mg/m ³	TWA: 50 ppm TWA: 260 mg/m ³ STEL: 75 ppm STEL: 325 mg/m ³	TWA: 50 ppm TWA: 260 mg/m ³ STEL: 100 ppm STEL: 520 mg/m ³
ACETIC ACID 64-19-7	STEL 20 ppm STEL 50 mg/m ³ MAK: 10 ppm MAK: 25 mg/m ³	STEL: 20 ppm STEL: 50 mg/m ³ MAK: 10 ppm MAK: 25 mg/m ³	NDSch: 30 mg/m ³ NDS: 15 mg/m ³	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm STEL: 37.5 mg/m ³	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 15 ppm STEL: 37 mg/m ³
BENZALDEHYDE 100-52-7	-	-	STEL: 40 mg/m ³ TWA: 10 mg/m ³	-	-
LIMONENE 5989-27-5	-	STEL: 40 ppm STEL: 220 mg/m ³ MAK: 20 ppm MAK: 110 mg/m ³	-	TWA: 25 ppm TWA: 140 mg/m ³ STEL: 37.5 ppm STEL: 175 mg/m ³	-
PINENES 80-56-8	-	-	-	TWA: 25 ppm TWA: 140 mg/m ³ Skin STEL: 37.5 ppm	-

				STEL: 175 mg/m ³	
--	--	--	--	-----------------------------	--

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Tightly fitting safety goggles.

Skin and body protection Antistatic boots. Wear fire/ flame resistant/ retardant clothing. Impervious gloves.

Respiratory protection NIOSH/MSHA approved respiratory protection is required to be worn.

Environmental Exposure Controls No information available.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	liquid
Appearance	clear
Aroma	peach
Color	colorless

<u>Property</u>	<u>Values</u>	<u>• Method</u>
pH		No information available
Melting/freezing point		No information available
Boiling point/boiling range		FCC Method
Flash Point	22 °C / 71 °F	Closed cup
Evaporation rate		FCC Method
Flammability (solid, gas)		No information available
Flammability Limits in Air		
Upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure mm Hg 20°C		No information available
Vapor density		No information available
Relative density		No information available
Specific Gravity @ 25C	0.882 - 0.902	FCC Method
Specific Gravity @ 20C	0.885 - 0.905	FCC Method
Refractive Index	1.365 - 1.385	FCC Method
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient: n-octanol/water		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic		No information available
Viscosity, dynamic		No information available
Explosive properties	No information available	
Oxidizing Properties	No information available	

9.2. Other information

Softening point	No information available
Molecular Weight	No information available
VOC Content(%)	No information available
Density VALUE	No information available
Bulk Density VALUE	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact none.
Sensitivity to Static Discharge Yes.

10.3. Possibility of hazardous reactions

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

None under normal use conditions.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

Inhalation There is no data available for this product.
Eye contact There is no data available for this product.
Skin contact There is no data available for this product.
Ingestion There is no data available for this product.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 5,850.00 mg/kg
ATEmix (dermal) 6,205.00 mg/kg
ATEmix (inhalation-dust/mist) 1.18 mg/l
ATEmix (inhalation-vapor) 23.00 mg/l

Unknown Acute Toxicity

96.679195% of the mixture consists of ingredient(s) of unknown toxicity.
20.300195 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
87.460295 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
96.679195 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
93.679195 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
29.519125 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Oral LD50

Chemical Name	Oral LD50	Dermal LD50	LC50 Inhalation
ETHYL ALCOHOL	7060 mg/kg (Rat)		124.7 mg/L (Rat) 4 h

ETHYL ACETATE	5620 mg/kg (Rat)	20 mL/kg (Rabbit)	
CITRIC ACID	3000 mg/kg (Rat)		
BENZYL ALCOHOL	1230 mg/kg (Rat)	2000 mg/kg (Rabbit)	8.8 mg/L (Rat) 4 h
ISOAMYL ACETATE	16600 mg/kg (Rat)	5 g/kg (Rabbit)	

Skin corrosion/irritation	No information available.
Eye damage/irritation	No information available.
Sensitization	No information available.
Germ Cell Mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
Specific target organ systemic toxicity (single exposure)	No information available.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Target Organ Effects	Blood, Central nervous system, Eyes, Liver, Reproductive system, Respiratory system, Skin.
Aspiration hazard	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Toxic to aquatic life

20.0332% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
ETHYL ALCOHOL	-	12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static
ETHYL ACETATE	3300: 48 h Desmodesmus subspicatus mg/L EC50	220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	560: 48 h Daphnia magna mg/L EC50 Static
BENZYL ALCOHOL	35: 3 h Anabaena variabilis mg/L EC50	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50
ACETIC ACID	-	75: 96 h Lepomis macrochirus mg/L LC50 static 79: 96 h Pimephales promelas mg/L LC50 static	47: 24 h Daphnia magna mg/L EC50 65: 48 h Daphnia magna mg/L EC50 Static
HEXYL ALCOHOL	-	89.7 - 106: 96 h Pimephales promelas mg/L LC50 flow-through 144: 96 h Brachydanio rerio mg/L LC50 static	201: 24 h Daphnia magna mg/L EC50
BENZALDEHYDE	-	10.6 - 11.8: 96 h Oncorhynchus	50: 24 h Daphnia magna mg/L

		mykiss mg/L LC50 flow-through 12.69: 96 h Oncorhynchus mykiss mg/L LC50 static 0.8 - 1.44: 96 h Lepomis macrochirus mg/L LC50 flow-through 6.8 - 8.53: 96 h Pimephales promelas mg/L LC50 flow-through 7.5: 96 h Lepomis macrochirus mg/L LC50 static	EC50
LIMONENE	-	0.619-0.796: 96 h Pimephales promelas mg/L LC50 flow-through 35: 96 h Oncorhynchus mykiss mg/L LC50	-
PINENES	-	0.28: 96 h Pimephales promelas mg/L LC50 static	41: 48 h Daphnia magna mg/L LC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	log Pow
ETHYL ALCOHOL	-0.32
ETHYL ACETATE	0.6
BENZYL ALCOHOL	1.1
ACETIC ACID	-0.31
HEXYL ALCOHOL	2.03
BENZALDEHYDE	1.48
PINENES	4.1

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Empty remaining contents.

Section 14: TRANSPORT INFORMATION

IMDG / IMO

14.1 UN/ID No 1993

14.2 Proper shipping name	FLAMMABLE LIQUID, N.O.S. (ETHYL ALCOHOL, ETHYL ACETATE)
14.3 Hazard class	3
14.4 Packing Group	II

DOT/ADR/RID

14.1 UN/ID No	1993
14.2 Proper shipping name	FLAMMABLE LIQUID, N.O.S. (ETHYL ALCOHOL, ETHYL ACETATE)
14.3 Hazard class	3
14.4 Packing Group	II

ICAO/IATA

14.1 UN/ID No	1993
14.2 Proper shipping name	FLAMMABLE LIQUID, N.O.S. (ETHYL ALCOHOL, ETHYL ACETATE)
14.3 Hazard class	3
14.4 Packing Group	II
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

International Inventories

TSCA	-
DSL/NDSL	-
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECL	-
PICCS	-
AICS	-

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of R-phrases referred to under sections 2 and 3**

R11 - Highly flammable
 R66 - Repeated exposure may cause skin dryness or cracking
 R67 - Vapors may cause drowsiness and dizziness
 R36 - Irritating to eyes
 R10 - Flammable
 R20/22 - Harmful by inhalation and if swallowed

Full text of H-Statements referred to under section 3

H333 - May be harmful if inhaled
 H302 - Harmful if swallowed
 H401 - Toxic to aquatic life
 H319 - Causes serious eye irritation
 H227 - Combustible liquid
 H332 - Harmful if inhaled
 H316 - Causes mild skin irritation
 H402 - Harmful to aquatic life
 H312 - Harmful in contact with skin
 H226 - Flammable liquid and vapor
 H225 - Highly flammable liquid and vapor
 H336 - May cause drowsiness or dizziness
 H400 - Very toxic to aquatic life
 H317 - May cause an allergic skin reaction
 H315 - Causes skin irritation
 H304 - May be fatal if swallowed and enters airways
 H410 - Very toxic to aquatic life with long lasting effects
 H318 - Causes serious eye damage
 H303 - May be harmful if swallowed
 EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorization:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA:	Time weighted average	STEL:	Short term exposure limit
Ceiling:	Maximum limit value:	*	Skin designation

Revision Date 30-Jul-2019

Reason for revision: Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

WARNING/DISCLAIMER:

Apex Flavors, Inc.'s products are sold exclusively for use in food and drink for human consumption. These products have not been tested, nor have they been deemed safe, for inhalation or use in electronic smoking devices, electronic nicotine delivery systems, and electronic cigarettes or similar devices (collectively "E-Cigarettes"). In supplying this product(s), Apex Flavors, Inc. instructs, and purchasing recipient confirms, that this product(s) will not be used in connection

with the manufacture and distribution of E-Cigarettes or any component thereof. Recipients of our products that use them outside of their intended use of food or drink do so at their own risk and without warranty, either expressed or implied, from Apex Flavors, Inc. or its suppliers. The user assumes all liability for loss, injury, damage, or expense resulting from such uses.